

Version 2018 扩径接头



产品特征

- 把原本较小的螺纹转换成稍大的螺纹
- 材质可选不锈钢、碳钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅胶
- 可用于爆炸性氛围IIA IIB IIC

符合标准

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

订货编号	外螺纹	内螺纹	螺纹长度	主体高度	扳手径
公制转公制	AG(M)	AG(F)	L	H+L	SW
CR-M12(M)/M16(F)	M12*1.5	M16*1.5	14	32	19
CR-M16(M)/M18(F)	M16*1.5	M18*1.5	14	32	22
CR-M16(M)/M20(F)	M16*1.5	M20*1.5	14	32	24
CR-M18(M)/M20(F)	M18*1.5	M20*1.5	14	32	24
CR-M20(M)/M24(F)	M20*1.5	M24*1.5	15	33	27
CR-M20(M)/M25(F)	M20*1.5	M25*1.5	15	33	29
CR-M24(M)/M30(F)	M24*1.5	M30*1.5	15	33	34
CR-M24(M)/M32(F)	M24*1.5	M32*1.5	15	33	36
CR-M25(M)/M30(F)	M25*1.5	M30*1.5	15	33	34
CR-M25(M)/M32(F)	M25*1.5	M32*1.5	15	33	36
CR-M30(M)/M40(F)	M30*1.5	M40*1.5	16	36	45
CR-M32(M)/M40(F)	M32*1.5	M40*1.5	16	36	45
CR-M40(M)/M50(F)	M40*1.5	M50*1.5	16	36	55
CR-M50(M)/M60(F)	M50*1.5	M60*1.5	18	40	65
CR-M50(M)/M63(F)	M50*1.5	M63*1.5	18	40	68
CR-M63(M)/M75(F)	M63*1.5	M75*1.5	18	41	80

订货编号	外螺纹	内螺纹	螺纹长度	主体高度	扳手径
美制转公制	AG(M)	AG(F)	L	H+L	SW
CR-NPT1/2(M)/M20(F)	NPT1/2	M20*1.5	14	32	24
CR-NPT1/2(M)/M25(F)	NPT1/2	M25*1.5	15	33	29
CR-NPT3/4(M)/M30(F)	NPT3/4	M30*1.5	15	33	34
CR-NPT3/4(M)/M32(F)	NPT3/4	M32*1.5	15	33	36
CR-NPT1(M)/M40(F)	NPT1	M40*1.5	16	35	45
CR-NPT1¼(M)/M50(F)	NPT1-1/4	M50*1.5	16	35	55
CR-NPT1¼(M)/M60(F)	NPT1-1/4	M60*1.5	16	36	65
CR-NPT1½(M)/M50(F)	NPT1-1/2	M50*1.5	16	36	55
CR-NPT1½(M)/M60(F)	NPT1-1/2	M60*1.5	16	36	65
CR-NPT1½(M)/M63(F)	NPT1-1/2	M63*1.5	16	37	68
CR-NPT2(M)/M63(F)	NPT2	M63*1.5	18	39	68
CR-NPT2(M)/M75(F)	NPT2	M75*1.5	18	41	80
CR-NPT2½(M)/M75(F)	NPT2-1/2	M75*1.5	24	46	80
CR-NPT2½(M)/M87(F)	NPT2-1/2	M87*1.5	24	46	92
CR-NPT3(M)/M87(F)	NPT3/4	M87*1.5	25	52	92
CR-NPT3(M)/M100(F)	NPT3	M100*2.0	25	52	108

内外螺纹可根据客户要求定制

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better world

Version 2018 缩径接头



产品特征

- 把原本较大的螺纹转换成稍小的螺纹
- 材质可选不锈钢、碳钢或黄铜镀镍
- 密封件可选丁腈橡胶或硅胶
- 可用于爆炸性氛围IIA IIB IIC

符合标准

应用行业

适用环境

防爆标记

防护等级

产品认证

可选附件

订货编号	外螺纹	内螺纹	螺纹长度	主体高度	扳手径
英制转公制	(M)	(F)	L mm	H mm	SW
CR-G1/2(M)/M16*1.5(F)	G1/2	M16*1.5	15	19	24
CR-G3/4(M)/M20*1.5(F)	G3/4	M20*1.5	15	19	30
CR-G1(M)/M25*1.5(F)	G1	M25*1.5	15	19	36
CR-G1¼(M)/M32*1.5(F)	G1-1/4	M32*1.5	15	19	45
CR-G1½(M)/M40*1.5(F)	G1-1/2	M40*1.5	15	20	52
CR-G2(M)/M50*1.5(F)	G2	M50*1.5	16	22	65
CR-G2½(M)/M63*1.5(F)	G2-1/2	M63*1.5	18	24	80
CR-G3(M)/M75*1.5(F)	G3	M75*1.5	20	26	95
CR-G3½(M)/M87*1.5(F)	G3-1/2	M87*1.5	20	26	108
CR-G4(M)/M100*2.0(F)	G4	M100*2.0	22	29	122

订货编号	外螺纹	内螺纹	螺纹长度	主体高度	扳手径
美制转英制	(M)	(F)	L mm	H mm	SW
CR-N1/2(M)/G3/8(F)	NPT1/2	G3/8	15	19	24
CR-N3/4(M)/G1/2(F)	NPT3/4	G1/2	15	19	30
CR-N1(M)/G3/4(F)	NPT1	G3/4	16	20	36
CR-N1¼(M)/G1(F)	NPT1-1/4	G1	16	20	45
CR-N1½(M)/G1¼(F)	NPT1-1/2	G1-1/4	16	21	52
CR-N2(M)/G1½(F)	NPT2	G1-1/2	18	24	65
CR-N2½(M)/G2(F)	NPT2-1/2	G2	24	30	80
CR-N3(M)/G2½(F)	NPT3	G2-1/2	25	31	95
CR-N3½(M)/G3(F)	NPT3-1/2	G3	27	33	108
CR-N4(M)/G3½(F)	NPT4	G3-1/2	28	35	122

内外螺纹可根据客户要求定制

Email:sales@idl-cr.com
Web: www.ex-cablegland.com
www.idl-cr.com

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice

IDL&CR·昂得立®
power and productivity
for a better world